



MINIMAX-E

- Recovers all commonly used CFC, HFC, HCFC refrigerants including R410A
- Minimum size – maximum performance; ideal for residential and appliance service
- Proprietary “oil-less” compressor capable of handling both liquid and vapor refrigerants
- Ergonomic design for easier handling
- Tough corrosion proof polyethylene blow molded case
- Field serviceable semi-hermetic compressor
- Self purge feature
- Includes filter-drier
- New Generation Compressor, new valves and piston
- New long 2,5 m removable cable
- 38,5 bar (550 psi) safety cut off switch
- Power Source – 230 V 50/60 Hz
- Available 115 V / 60 Hz
- CE, TÜV approved
- Weight: 11 kg
- Dimensions: 250 x 222 x 406 mm (11" x 9" x 16")



CP1320

New Generation “oil-less”
compressor CP1320,
new valves and piston

MINIMAX-E

High Pressure Recovery Unit



International Versions	Model No.
UK, 115 V / 60 Hz	Minimax USA

Optional Accessories	Part Number
12,5 kg Recovery Tank	RGT30NS
26 kg Recovery Tank	RGT50NS

Replacement Parts (supplied with product)	Part Number
Filter-Drier, 1/4" MFL x 1/4" MFL	100343
Hose, Blue 10 cm (4") Long	100345