



RG5410A-E

- Recovers all commonly used CFC, HFC, HCFC refrigerants including R410A
- Designed for use with high pressure refrigerants
- High Pressure safety "cut off" switch 38,5 bar (550 psi)
- Proprietary "oil-less" compressor capable of handling both liquid and vapor refrigerants
- New long 2,5 m removable cable
- VAC Sensor Select, selectable low pressure ON/OFF switch
- New Generation Compressor, new valves and piston
- Easier access to high pressure switch
- Includes filter-drier • Self purge feature
- All new ergonomic design for easier handling
- 3/8" – 3-row condenser for maximum performance in even the hardest conditions
- Corrosion proof polyethylene blow molded case
- Field serviceable semi-hermetic compressor
- Power source – 230 V 50/60 Hz
- Available 115 V / 60 Hz
- CE, TÜV approved
- Weight: 13,5 kg
- Dimensions: 343 x 229 x 483 mm (13" x 9" x 19")



CP1320

New Generation "oil-less" compressor CP1320, new valves and piston

PROMAX RG5410A-E High Pressure Recovery Unit



RG5410A-E inside view

International Version	Part Number
UK, 115 V / 60 Hz	RG5410A-E 115 V / 50/60 Hz

Optional Accessories	Part Number
12,5 kg Recovery Tank	RGT30NS
26 kg Recovery Tank	RGT50NS

Replacement Parts (supplied with product)	Part Number
Filter-Drier, 1/4" MFL x 1/4" MFL	100343
Hose, Blue 10cm (4") Long	100345

